

PASLANMAZ ÇELİK ÇOK KADEMELİ SANTRİFÜJ POMPALAR

GENEL ÖZELLİKLER

> Sıvıya temas eden tüm parçalar AISI 304 Paslanmaz Çelik

ÇALIŞMA KOŞULLARI

- > Max. su sıcaklığı 80 °C
- > MAX. ortam sıcaklığı 40 °C
- > Emiş derinliği 6.5 m'ye kadar



POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ											
							m³/h	0	0.8	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.4
TPSH206M *50lt.	1	220	1"	1"	416	170	h(m)	56	53	51	49	47	44	41	37	32	26	-
TPSH206T *50lt.	1	380	1"	1"	416	188		56	53	51	49	47	44	41	37	32	26	-
TPSH207M *50lt.	1.5	220	1"	1"	416	200		67	63	61	59	58	54	50	47	42	37	27
TPSH207T *50lt.	1.5	380	1"	1"	416	188		67	63	61	59	58	54	50	47	42	37	27

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ											
							m³/h	0	1	2	3	3.5	4	4.5	5	5.5	6	7
TPSH406M *50lt.	1.8	220	1¼"	1"	446	209	h(m)	60	58	56	54	51	50	48	46	42	38	27
TPSH406T *50lt.	1.8	380	1¼"	1"	446	211		60	58	56	54	51	50	48	46	42	38	27
TPSH407M *50lt.	2	220	1¼"	1"	446	209		70	67	65	63	61	60	56	53	50	44	31
TPSH407T *50lt.	2	380	1¼"	1"	446	211		70	67	65	63	61	60	56	53	50	44	31

POMPA TİPİ	GÜÇ HP	VOLT V	GİRİŞ	ÇIKIŞ	L (mm)	H (mm)	DEBİ											
							m³/h	0	2	4	6	7	8	9	10	12	14	16
TPSH802M *50lt.	2	220	1½"	1½"	408	232	h(m)	50	46	43	38	34	30	25	20	-	-	-
TPSH802T *50lt.	2	380	1½"	1½"	408	217		50	46	43	38	34	30	25	20	-	-	-
TPSH804M *50lt.	3	220	1½"	1½"	479	244		70	68	65	57	50	43	42	34	20	-	-
TPSH804T *50lt.	3	380	1½"	1½"	438	217		70	68	65	57	50	43	42	34	20	-	-